

Manhole: \$38 Hiahway Drain

Mannele: 666 highway brain								
MH Ref:	Cover Level	Invert Level	Depth to soffit	Pipe Dia	МН Туре	MH Size		
HD1	2.300	1.425	0.650	225	Туре D	900x675		
HD2	2.450	1.320	0.905	225	Туре D	900x675		
HD3	2.750	1.600	1.000	150	Туре D	900x675		

Pipeline: \$38 Highway Drain

Pipe Ref:	Upstream IL	Downstream IL	Pipe Dia	Distance	Pipe Gradient 1:X	Pipe Gradient %	Pipe Material	
1.000	1.425	1.320	225	25.674	244.5	0.41%	Clayware	
1.001	1.320	1.300	225	5.000	250.0	0.40%	Clayware	
2.000	1.600	1.312	150	15.000	52.1	1.92%	Clayware	

MH Cover
D400
D400
D400

S38 Street Lighting Notes

- 1. Column foundations to be as per SD/14/2A 2. All columns to be provided with Distribution Network Operator (D.N.O.) Services and Termination Type A to LCC Standard Detail SD/14/4A unless otherwise specified. DNO Cutouts to be fitted with 16Amp BS88 Fuse Link. Double Pole Isolator to be fitted with BS 88 Fuse Link to L.C.C Appendix 14/4.
- Columns to be installed with doors at an angle to ensure operatives working on the column are facing oncoming traffic, unless otherwise agreed with LCC.
- Column setbacks shall comply with Table 2 Section 4.3.3.3 of BS 5489-1:2013.
- Columns shall not be installed within Drop Kerb areas and shall have a minimum clearance of 1.5m from Drives/Accesses.
- Trees must not be planted within 5 metres of 6. proposed lighting columns.
- 7. It is preferred that all Street Lighting works are
- undertaken by L.C.C Approved Contractors.
- 8. Lanterns to be cleaned (during Contractors. 8. Lanterns to be cleaned (during maintenance period)
- prior to adoption as detailed in \$38 Agreement. Developer to liaise with Distribution Network Operator
- (D.N.O.) with regards to connections and disconnections of columns and appropriate black ducting. Where an independent D.N.O. (I.D.N.O.) has been used the cutout must be clearly and indelibly marked with the I.D.N.O. name and contact number.
- 10. It is the Developers responsibility to inform property owners of part night street lighting switching where applicable.
- All private cabling shall have correct core colour identification as detailed in BS7671. Sleeving of conductors is not permitted.
- 12. Due to ongoing technical innovations within the industry, if the street lighting equipment is to be ordered in excess of three years after the drawing approval date, the Authority reserves the right to
- upgrade the equipment specification. Lighting has been designed to comply with 13. BS5489-1:2013 Lighting Class P5.



William Saunders is the trading name of Wm Saunders Partnership LLP. Wm Saunders Partnership Limited Liability Partnership is registered in England and Wales with the Registration number OC 308323. The Registered Office is Sheppard Lockton House, Cafferata Way, Newark on Trent, Notts. NG24 2TN.

This drawing & any design thereon is the copyright of Wm Saunders Partnership LLP and must not be reproduced without their written consent.

Contractors must verify all dimensions, levels and co-ordinates at the site before commencing any work or making any shop drawings: no dimensions to be taken from drawing.

ALL WORKS TO BE CONSTRUCTED IN ACCORDANCE WITH THE REQUIREMENTS OF LINCOLNSHIRE COUNTY COUNCILS DEVELOPMENT ROAD AND SUSTAINABLE DRAINAGE DESIGN GUIDE AND DEVELOPMENT ROAD AND SUSTAINABLE DRAINAGE SPECIFICATION AND CONSTRUCTION.

Notes:

1) "The specification in all respects shall be in accordance with the current Lincolnshire Development Road and Sustainable Drainage Design Guide" and "Development Road and Sustainable Drainage Specification and Construction" publications in force in the county at the time of construction.

2) The minimum longitudinal fall for highways, without channel blocks shall be 1 in 150, and with channel blocks 1 in 250 (see Clause 10.1).

3) In addition, ensure that the first section of any side road falls away from the road to which it is connecting. If general topography requires it to rise, this change of direction should take place after the first set of gullies. This is to ensure a 'false channel' with associated drainage problems is not created in the bellmouth of junctions.

4) "General deterioration of the existing highway/footway/verges created through construction of the new Section 38 Development will be reinstated to the current Development Road Specification at the developers' own cost at the agreement of the inspecting Highway and Flood Authority Officer".

5) "No Private surface water shall discharge onto the adoptable highway"

6) "No private, structural features shall overhang the adoptable highway".

7) "No private retaining walls exceeding 1.37m shall be within 3.66m of the highway boundary".

P4	Background detail updated	PAE	PAE	23/10/20			
P3	Revised to suit comments from LCC.	JW	PAE	30/03/20			
P2	Revised to suit comments from LCC, contours amended to suit revised levels, PN 2.000 rev.	WL	PAE	28/02/20			
P1	Initial issue	JW	PAE	14/02/20			
Rev	Description	Drn	Vf'd	Date			
As outlined in section 2.3 of the CITB Industry Guidance to Designers, insignificant risks can usually be ignored, as can risks arising from routine construction activities, unless the design compounds or significantly alters these risks. In accordance with CDM Regulations 8, 9 and 11, any significant risks relating to the design features shown on this drawing have been identified and are annotated thus:							
Des	signer's Signature	Da	te O	2/20			
Drawing Status REGULATORY APPROVAL							

williamsaunders

architecture: engineering: building consultancy Sheppard Lockton House Cafferata Way

Newark-on-Trent Nottinghamshire. NG24 2TN

Tel: 01636 704361 Fax: 01636 702809 W: wm-saunders.co.uk

Also at Leeds, Lincoln, Wirksworth

Project

Proposed Residential Development Land off Fenside Road, Boston

Client Seagate Homes (UK) Ltd

Title COO Cont

S38 Contours							
WmS Project Ref.	Drawn	Date 02/2020	Scale 1·500	@ A1			
Drawing/Document Reference							
Project Origina	tor Zone 1 S - ZZ	Level Type R - XX - DR - (ole Number C - 39504 ·	Status Rev. - S8 - P4			