

PLAIN FROST

Frosted privacy films are designed to provide protection against the scrutiny of prying eyes. Whilst completely opalescent, it still allows most natural light to pass through.



PURLFROST® Warranty
5 YEARS



Storage from -5°C to +40°C
3 YEARS



REACH RoHS compliant
RESPECTED

WIDTHS AVAILABLE:

↔ **100 cm 122 cm**


TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	55 %
Visible light transmission	90 %
Reflection of external visible light	15 %
Reflection of internal visible light	15 %
Total solar energy rejected	18 %
Total solar energy rejected 2	19 %
Solar ratio :	
Solar energy reflection	10 %
Solar energy absorption	17 %
Solar energy transmission	73 %
Reduction in Solar Glare	20 %
g-value	0.77
u-value	5.6
Shading coefficient	NC
Installation type : Internal application	
Roll length	50 m
PET / PVC composition	PVC
Thickness	90 µ
Colour : FROSTED	

CONSTRUCTION

1. 100µ Frosted monomer PVC
2. Half Permanent Adhesive, allowing the "degassing" of the actual surface, and limits the adhesive transfer during removal
3. Protection release liner, disposable after installation



INSTALLATION ADVICE

Vertical installation and on standard glass surface*

Clear single pane	✓
Tinted single pane	✓
Reflective tinted single pane	✓
Clear double pane	✓
Tinted double pane	✓
Reflective tinted double pane	✓
Gas-filled double pane - Low E	✓
STADIP EXT. clear double pane	✓
STADIP INT. clear double pane	✓

✓ Yes ⚠ Caution ✗ No

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

MAINTENANCE INSTRUCTIONS

Soapy water solution, do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data, PURLFROST® reserves the right to modify the composition of its films at any time.